

code 124112200000300




Infra Red



Forced Air  
(optional)

## Infra-Red Radiant Panels Dryers



## Features

“Noir” is a high speed dryer designed to quickly cure Plastisol inks on fabrics.

- Precise electronic temperature regulator which acts directly on radiant panel temperature.
- High quality drying thanks to special radiant panels which no drying quality differences for light or dark colors.
- Perfect belt alignment thanks to an air-operated centering device and tensioning system that automatically compensates any stretch.
- Tunnel height can be adjusted to position the radiant panels at will to optimize drying performance.
- Cladding panels are perfectly insulated by adopting special technical measures and excellent quality materials.
- The outer surface always remains at ambient temperature, thereby reducing dispersion of heat.
- Provided with extraction fan for expulsion of exhaust fumes.

## Optionals

- Forced air system to dry water-based inks
- Increase entrance height to 300mm
- Conveyor belt wide 1600mm
- Inlet and outlet extensions
- Outlet cooling system



Noir 3750 with combined IR / Air system and heating chamber height increased to 300mm

Main Application: Screen Printing - Industrial production

code 124112200000300

## Configurations

### Noir 2500

Curing Area: 2500x1050 mm

Power: 15,5 kW

Production: 450 pieces/h



TECHNICAL DATA	NOIR 2500
Power Supply	400V 3P+N+PE - 25 A
Exhaust Specification	600 m <sup>3</sup> /h - Ø 125 mm
Max Temperature (IR Panels)	550°C
Power Consumption (max)	16 kW
Belt Width [mm]	1050
Tunnel Length [mm]	2500
Production <sup>1</sup>	450 pieces/h
Dimension <sup>2</sup> (LxWxH)[mm]	4500 x 1380 x 1640
Shipping Weight	660 kg

<sup>1</sup> Production of T-shirts with A4 print size - 1,5 minutes curing time

<sup>2</sup> Dimension and Weight can change accordingly to inlet/outlet extensions or installed optionals.

Other configurations are available on demand

